

December 2007

PHENOL-FORMALDEHYDE BONDED WOOD PRODUCTS MSDS

<u>Manufacturer Name and Address</u>	<u>Effective Date</u>	<u>Supersedes Date</u>	<u>Prepared By</u>
The Penrod Company 2809 South Lynnhaven Road – Suite 350 Virginia Beach, VA 23452	12/11/2007	10/09/2006	M. Clausen

PRODUCT IDENTIFICATION:

Hardwood Plywood, Veneer Core
Platforms, Uniply, Lumber Core
Platforms, Particleboard, Medium
Density Fiberboard (Phenol-
Formaldehyde Bonded), Medium
Density Overlay*

SYNONYMS:

VCPF, Blanks, LCPF, 2-Ply,
Plywood, PB MDF, MDO

TRADE NAME:

None

DESCRIPTION:

This panel product contains a hardwood veneer face (occasionally a decorative softwood face) bonded to wood components such as other wood veneer, particleboard, or medium density fiberboard (MDF) using phenol-formaldehyde resin.

POTENTIAL AIRBORNE RELEASES:

The product may release small quantities of formaldehyde (CAS No. 50-00-0) in gaseous form. Emissions decrease through time as the panels age. Manual or mechanical cutting or abrasion processes performed on the product can result in generation of wood dust.

PHYSICAL DATA

Boiling Point..... Not applicable

Specific Gravity (H₂O = 1)..... <1

Vapor Density..... Not applicable

% Volatiles by Vol..... 0

Melting Point..... Not applicable

* This fact sheet is for products that have not been finished (coated, laminated, or overlaid) or treated (for example, with preservatives or fire retardant).

Vapor Pressure..... Not applicable
Solubility in H₂O (% by wt.)..... <0.1%
Evaporation Rate (Butyl Acetate = 1)..... Not applicable
pH..... Not applicable
Appearance and Odor..... Light to dark colored granular solid.
Color and odor are dependent on the
wood species.

FIRE AND EXPLOSION DATA

Flash Point..... Not applicable
Autoignition Temperature..... Not available (will depend upon
duration of exposure to heat source
and other variables)
Explosive Limits in Air..... See below under “Unusual Fire and
Explosion Hazards”
Extinguishing Media..... Water, Carbon Dioxide, Sand
Special Fire Fighting Procedures..... None
Unusual Fire and Explosion Hazards..... Sawing, sanding or machining can
produce wood dust as a by-product
which may present an explosion hazard
if a dust cloud contacts an ignition
source. An airborne concentration of
40 grams of dust per cubic meter of air
is often used as the LEL for wood dust.

REACTIVITY DATA

Conditions Contributing to Instability..... Stable under normal conditions.
Incompatibility..... Avoid contact with oxidizing agents.
Avoid open flame. Product may ignite
in excess of 400 degrees F.
Hazardous Decomposition Products..... Thermal and /or thermal oxidative
decomposition can produce irritating
and toxic fumes and gases, including

carbon monoxide, hydrogen cyanide, aldehydes, organic acids and polynuclear aromatic compounds.

Hazardous Polymerization..... Not applicable

HEALTH EFFECTS INFORMATION

Exposure Limits:

Formaldehyde..... OSHA PEL-TWA: 0.75 ppm
OSHA PEL-STEL: 2 ppm
ACGIH TLV-CEILING:0.3 ppm

Wood Dust..... OSHA PELK-TWA: 15.0 mg/m3 (total dust): 5.0mg/m3 (respirable fraction)

1

See important footnote below concerning OSHA PELs for wood dust

Wood Dust (Softwood)..... ACGIH TLV-TWA: 5.0mg/m3
ACGIH TLV-STEL (15 min.): 10.0mg/m3

Wood Dust (Certain hardwoods such as beech and oak)..... ACGIH TLV-TWA: 1.0 mg/m3

Eye Contact..... Gaseous formaldehyde may cause temporary irritation or a burning sensation. Wood dust can cause mechanical irritation.

Skin Contact..... Both formaldehyde and various species of wood dust may evoke allergic contact dermatitis in sensitized individuals.

Ingestion..... Not likely to occur.

¹ In AFL-CIO v. OSHA 965 F. 2d 962 (11th Cir.1992), the court overturned OSHA's 1989 Air Contaminants Rule, including the specific PELs for wood dust that OSHA had established at the time. The 1989 PELs were: TWA – 5.0mg/m3; STEL (15min.) – 10.0mg/m3 (all soft and hard woods, except Western red cedar); Western red cedar: TWA – 2.5mg/m3.

Wood dust is now officially regulated as an organic dust under the Particulate Not Otherwise Regulated (PNOR) or Inert or Nuisance Dust categories at PELs noted under the Health Effects Information section of this MSDS. However, a number of states have incorporated provisions of the 1989 standard in their state plans. Additionally, OSHA has announced that it may cite companies under the OSH Act General Duty Clause under appropriate circumstances for non-compliance with the 1989 PELs.

Gaseous formaldehyde..... May cause temporary irritation to eyes, nose, and throat. Some reports suggest that formaldehyde may cause respiratory sensitization, such as asthma, and the pre-existing respiratory disorders may be aggravated by exposure. Formaldehyde is listed by the International Agency for Research on Cancer (IARC) as a probable human carcinogen. The National Toxicology Program (NTP) includes formaldehyde in the Annual Report on Carcinogens. Formaldehyde is regulated by OSHA as a potential cancer agent. In studies involving rats, formaldehyde has been shown to cause nasal cancer from long-term exposure to very high concentrations (14 + ppm), far above those normally found in the workplace using this product. The National Cancer Institute (NCI) conducted an epidemiological study of industrial workers exposed to formaldehyde (published June 1986). The NCI concluded that the data provides little evidence that mortality from cancer is associated with formaldehyde exposure at the levels experienced by workers in the study.

Wood Dust..... May cause nasal dryness, irritation and obstruction. Coughing, wheezing, and sneezing; sinusitis and prolonged colds have also been reported.

Depending on species, may cause respiratory sensitization and/or irritation. IACR classifies wood dust as a carcinogen to humans (Group 1). This classification is based primarily on IARC's evaluation of increased risk in the occurrence of adenocarcinomas of the nasal cavities and paranasal sinuses associated with exposure to wood dust.

IARC did not find sufficient evidence to associate cancer of the oropharynx, lung, hypopharynx, lymphatic, stomach, and hematopoietic systems, colon or rectum with exposure to wood dust. The NTP includes wood dust in The Annual Report on Carcinogens.

PRECAUTIONS, SAFE HANDLING

Formaldehyde: Provide adequate ventilation to reduce the possible buildup of formaldehyde gas, particularly when high temperatures occur.

Wood Dust: Avoid dusty conditions and provide good ventilation.

GENERALLY APPLICABLE CONTROL MEASURES

Ventilation: Provide adequate general and local exhaust ventilation to keep airborne contaminant concentration levels below the OSHA PELs.

Personal Protective Equipment: Wear goggles or safety glasses when manufacturing or machining the product. Wear NIOSH/MSHA approved respirator when the allowable exposure limits may be exceeded. Other protective equipment such as gloves and outer garments may be needed depending on dust conditions.

EMERGENCY AND FIRST AID PROCEDURES

- Eyes..... Flush eyes with large amounts of water. Remove to fresh air. If irritation persists, get medical attention.
- Skin..... Wash affected areas with soap and water. Get medical advice if rash or persistent irritation or dermatitis occurs.
- Inhalation..... Remove to fresh air. Get medical advice if persistent irritation, severe coughing or breathing difficulty occurs.
- Ingestion..... Not applicable